

**MANUFACTURER:**

Firestone Textiles Co., A Division of Bridgestone Canada Inc.
1200 Dundas St. East, P.O. Box 486
Woodstock, Ontario N4S 7Y9, Canada

TELEPHONE: (519) 537-6231

I - MATERIAL IDENTIFICATION AND USE**CHEMICAL NAME AND SYNONYMS:**

Polycaprolactam; Polyamide 6; Nylon 6

CAS NUMBER:

25038 - 54 - 4

CHEMICAL FAMILY:

Polyamide polymers

FORMULA: $[NH(CH_2)_5CO]_n$ **CANADA - TRANSPORTATION OF DANGEROUS GOODS CLASSIFICATION:**

Not hazardous

CANADA - WHMIS CLASSIFICATION: Not a controlled article, not a manufactured article

U.S.A. - D.O.T. HAZARD CLASS: Not regulated

U.S.A. - RCRA STATUS OF UNUSED MATERIAL (40 CFR 261): Not hazardous

USES: Used to produce fabrics, ropes and nets.

II - INGREDIENTS

INGREDIENTS: Polycaprolactam 96% minimum
Polycaprolactam and proprietary additives

Proprietary ingredients may include such things as pigments and stabilizers. Some ingredients in their pure form are listed as hazardous. In nylon fibre, however, they are encapsulated and are not expected to present any hazards otherwise associated with them.

Contains less than 1.5% "finish", a combination of oils and emulsifiers to provide lubrication.

III - PHYSICAL DATA

PHYSICAL STATE:	solid	SPECIFIC GRAVITY:	1.12 - 1.15
MELTING POINT:	215 °C (420 °F)	ODOR:	nil
SOLUBILITY IN WATER:	nil	APPEARANCE:	colored fibers

IV - FIRE AND EXPLOSION DATA

FLAMMABILITY: Will ignite and burn above 250 °C (480 °F)

EXTINGUISHING MEDIA: Water, dry chemical, carbon dioxide

SPECIAL FIRE FIGHTING PROCEDURES: Firefighters and others exposed to products of combustion should wear self-contained breathing apparatus to avoid inhalation of combustion products.

V - REACTIVITY DATA

STABILITY: Stable at ambient temperatures

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing chemicals

CONDITIONS TO AVOID: Avoid direct contact with flame

HAZARDOUS DECOMPOSITION PRODUCTS: When burned, gases may contain CO and HCN

HAZARDOUS POLYMERIZATION: Will not occur

VI - HEALTH HAZARD DATATHRESHOLD LIMIT VALUE: None established for this material. However ACGIH have limits for "nuisance dusts" which is TLV - TWA = 10 mg/m³.

SKIN CONTACT: No known significant effects

VII - SPILL, LEAK & DISPOSAL INFORMATION

WASTE DISPOSAL: Dispose of waste nylon 6 as non-hazardous solid waste in accordance with federal state or provincial and local government regulations.

ENVIRONMENT: Nylon 6 does not biodegrade. If kept uncontaminated it can be reprocessed.

VIII - SPECIAL PROTECTION INFORMATION

PERSONAL PROTECTIVE EQUIPMENT: None under normal conditions.

RESPIRATORY PROTECTION: None under normal conditions.

IX - SPECIAL PRECAUTIONS

HEAT TREATMENT: If heated to elevated temperatures during processing, some of the "finish" oils may be evaporated. Such processes should be totally enclosed and properly ventilated. Inhalation of fumes and vapours is to be avoided, wear a respirator if necessary.

X - PREPARATION OF MSDS

PREPARED BY: D. Irwin PHONE: (519) 537-6231

DATE: January 8, 1998

REVIEWED BY: Kim Davie PHONE: (519) 537-6231

DATE: January 3, 2014

This information is given in good faith based on the best available knowledge of this specific product, however Bridgestone Canada Inc. provides no warranties, either expressed or implied, and assumes no responsibility as to the accuracy or completeness of this information.

Data on this Material Safety Data Sheet applies only to the product described and may not be relevant to use in combination with other materials, or in any process.